



ASSEMBLY INSTRUCTION MODEL OLL-6008-AG-BH



All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.



You will need 21 Candelabra Base Bulb
40 Watts Recommended 60 Watts Max.
USE LED BULBS FOR EXTENDED USE
(This fixture is Dry rated)



How to Install


1. Decide the preferred hanging height and choose the correct length of chain needed.
2. Feed the fixture wire and the safety cable through the top stem, and screw the stem onto the frame.
3. Attach one end of the 1/4 IPS threaded pipe provided onto the ceiling joist and secure with hex nut. The other end should protrude through the outlet box as shown.
4. Assemble the screw collar loop, nipple hex nut and hickey to the 1/4 IPS threaded pipe and adjust overall length to allow the collar ring to hold the canopy flush to ceiling.
5. Attach one end of the chain to the fixture loop by opening the quick link. Slide the screw collar ring over the upper end of the chain. Open the opposite quick link and lift the fixture to attach the screw collar loop to the quick link. Secure the link.
6. Feed the fixture wires, ground wires and safety cable through the chain and screw collar loop, exiting through the Hickey. Proceed with the wire connections. Wrap the safety cable around the ceiling joist and secure the cable with the clamp and set screws provided as shown. After wires are connected. Place the canopy up against the ceiling and lock by tightening the screw collar loop ring.
7. While raising the bottom light cluster up, insert the male plug from it to the female plug from the bottom of the frame. Carefully tuck the wires and plugs inside the tubing and secure it onto the bottom coupling using the screws.
8. Install recommended bulb into the socket
9. Dress the glass as illustrated

Glass Sets

1. 127 pcs Blush glass W3.25"xH11.5 "

WARNING: This product can expose you to Lead, which is known to the State of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov

PART NUMBER MODEL **OLL-6008-AG-BH**



Part Number

Part Numbers

A. Heavy duty mounting hardware

For 50lbs rated outlet box

- (1)-Long threaded rod
- (1)-Hickey
- (1)-Short threaded pipe
- (3)-Metal washer
- (1)-Hex nut

For 100lbs rated outlet box

- (1)-Thread pipe
- (2)-Two machine screws
- (1)-Coupling with set screws
- (1)-Hex nut

B.(1)-Canopy,D 5.5"XH1"
(XBN6006AGCAN5.5IN)

C.(1)-Collar ring

D.(1)-Collar loop

E.(1)-Chain,D6MM,L72"
(XBN6008AGCHA6MM)

F.(1)-Fixture loop,D2.5"


G.(1)-Center Stem,D0.75"*H9"
(XBN6006AGSTEM9IN)

H.(1)-Frame

I. (127)-Glass,W3.25" xH11.5"

J.(1)-Bottom light cluster

SAFETY CABLE INSTALLATION INSTRUCTIONS



IMPORTANT:

FOR A SAFE AND SECURE INSTALLATION, THESE FIXTURES MUST BE INSTALLED BY MEANS OF SUPPORTS THAT ARE INDEPENDENT OF THE OUTLET BOX.

SUGGESTED INSTALLATION: 1. Provide a 1/4 IPS pipe with one end securely mounted to a beam or a structural member.

The other end should protrude through the center of the outlet, as shown.

2. Assemble the screw collar loop, nipple, hex nuts and hickey to center 1/4 IPS support pipe and adjust overall length to allow the collar ring to hold the canopy flush to the ceiling. When the adjustments have been completed secure the hex nut, as shown.
3. Use one quick link to connect fixture loop and the bottom of chain. Slide the screw collar ring over the upper end of the chain, through the (Finished side down). Then use another quick link to connect collar loop and the top of chain.
4. Lace the fixture wires, ground wires and safety cable through the chain and screw collar loop, exiting through the side of HICKEY. Proceed to attach the FIXTURE GROUND WIRE to HOUSE GROUND WIRE using wire connector. Using wire connectors, connect the HOUSE WHITE WIRE to the FIXTURE SUPPLY WIRE (WHITE OR RIBBED SIDE); connect the HOUSE BLACK (or RED) WIRE to the FIXTURE SUPPLY WIRE (BLACK or SMOOTH SIDE). Wrap all connectors with approved electrical tape. Wrap safety cable around outlet box brace and pull cable taut. Secure cable with the clamp and (2) set screws provided, as shown.
5. Push the CANOPY upward over the OUTLET BOX. Be sure that all wires are carefully tucked into the OUTLET BOX cavity. Secure canopy against ceiling by threading CANOPY LOCK RING onto the CANOPY LOOP. Tighten until snug.