

WAC LIGHTING

Fido

Outdoor Wall Sconce 4CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
○ WSW106616 16"	2700K/3000K/3500K/4000K	○ BK Black	11W	1100	91

Example: **WSW106616-BK**
For custom requests please contact customs@wacighting.com

DESCRIPTION

Faithful in form and function, Fido is a loyal design companion for your home's exterior. With a sculptural, bone-inspired silhouette and balanced up-and-down LED illumination Fido is built to brighten your nights.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Light engine is factory sealed for maximum protection from the elements
- Up/Down light with illuminator from center collar
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120V,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall vertically or horizontally
Standards:	ETL, cETL, Wet Location Listed
Construction	Aluminum body with silicone diffuser




FINISHES:



Black

LINE DRAWING



WSW106616

WAC LIGHTING

Fido

Outdoor Wall Sconce 4CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
○ WSW106624 24"	2700K/3000K/3500K/4000K	○ BK Black	16.6W	1600	193

Example: **WSW106624-BK**
For custom requests please contact customs@wacighting.com

DESCRIPTION

Faithful in form and function, Fido is a loyal design companion for your home's exterior. With a sculptural, bone-inspired silhouette and balanced up-and-down LED illumination Fido is built to brighten your nights.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Light engine is factory sealed for maximum protection from the elements
- Up/Down light with illuminator from center collar
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120V,50/60Hz
CRI	90
Dimming:	ELV: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on wall vertically or horizontally
Standards:	ETL, cETL, Wet Location Listed
Construction	Aluminum body with silicone diffuser




FINISHES:



Black

LINE DRAWING



WSW106624